

Libraries

Name	Process	Form Factor
RGO_TSMC06_18V18_6FF_20F_3VT	6FF	Staggered Flip Chip
RGO_TSMC07_18V18_7FF_20C_3VT	7FF	Staggered Flip Chip

Summary

The 1.8V GPIO 3VT library provides general purpose bidirectional I/O cells that are both fault tolerant and 3.3V tolerant. These programmable, multi-voltage I/O's give the system designer the flexibility to design to a wide range of performance targets.

This library is offered at both 6nm and 7nm. It is available in a staggered flip chip implementation.

To design an operational I/O power domain with these cells, an additional library is required – 3.3V Support: Power. That library contains an input-only buffer, isolated analog I/O, and a full complement of power cells along with corner and spacer cells to assemble a functional pad ring by abutment. An included rail splitter allows multiple power domains to be isolated in the same pad ring while maintaining continuous VDD/VSS for robust ESD protection.

ESD Protection:

- JEDEC compliant
 - 2kV ESD Human Body Model (HBM)
 - 500 V ESD Charge Device Model (CDM)

Latch-up Immunity:

- JEDEC compliant
 - Tested to I-Test criteria of $\pm 100\text{mA}$ @ 125°C


Cell Size & Form Factor

- Staggered (pad-limited) – 34.08 μm x 191.28 μm
- Flip chip implementation with CUP structure built in

Recommended Operating Conditions

Description	Min	Nom	Max	Units
V _{VDD} Core supply voltage	0.675	0.75	0.825	V
	1.62	1.8	1.98	V
V _{DVDD} I/O supply voltage	1.35	1.5	1.65	V
	1.08	1.2	1.32	V
T _J Junction temperature	-40	25	125	°C
V _{PAD} Voltage at PAD	V _{DVSS} -0.3	-	3.63	V

FRP_BI_SMB_33T_STB



Bidirectional GPIO Driver Features

- 3.63V tolerant (max) @1.8V operation
- Fault tolerant - no current flow when DVDD = 0V at V_{PAD} ≤ 3.63V
- Multi-Voltage (1.2V, 1.5V, 1.8V)
- LVCMOS / LVTTTL input with selectable hysteresis
- Programmable drive strength (rated 2mA to 12mA)
- Selectable output slew rate
- Optimized for EMC with SSO factor of 8
- Open-drain output mode
- Programmable input options (hi-Z/pull-up/pull-down/repeater)
- Power sequencing independent design with Power-On Control

In full-drive mode, this driver can operate to frequencies in excess of 100MHz with 15pF external load and 125 MHz with 10pF load. Actual frequency limits are load and system dependent. A maximum of 200 MHz can be achieved under small capacitive loads.

Characterization Corners

Model [1]	LPE Type	VDD=0.75V	DVDD [2]	Temp
FF	Cbest_CCbest	+10%	+10%	-40°C
FF	Cbest_CCbest	+10%	+10%	0°C
FF	Cbest_CCbest	+10%	+10%	125°C
FFG	Ctypical	+10%	+10%	125°C
TT	Ctypical	nominal	nominal	25°C
TT	Ctypical	nominal	nominal	85°C
SS	Cworst_CCworst	-10%	-10%	-40°C
SS	Cworst_CCworst	-10%	-10%	0°C
SS	Cworst_CCworst	-10%	-10%	125°C

[1] Listed models are for 7FF. 6FF models are FFGNP / TT / SSGNP.
 [2] DVDD = 1.8V, 1.5V & 1.2V

© 2011-2022 Aragio Solutions. All rights reserved.

Information in this document is subject to change without notice. Aragio Solutions may have patents, patent applications, trademarks, copyrights or other intellectual property rights covering subject matter in this document. Except as expressly provided in any written license agreement from Aragio, the furnishing of this document does not give you any license to the patents, trademarks, copyrights, or other intellectual property.

Published by:

Aragio Solutions
2201 K Avenue
Section B Suite 200
Plano, TX 75074-5918
Phone: (972) 516-0999
Fax: (972) 516-0998
Web: <http://www.aragio.com/>

While every precaution has been taken in the preparation of this book, the publisher assumes no responsibility for errors or omissions, or for damages resulting from the use of the information contained herein. This document may be reproduced and distributed in whole, in any medium, physical or electronic, under the terms of a license or nondisclosure agreement with Aragio.

Printed in the United States of America